

Architectural Specifications

Collegiate 4000 Volleyball Net System – Complete System

COLLEGIATE 4000 POST

MODEL NO. SNAVB41C4N

Removable type, in-floor sleeves. Uprights shall be one single piece, 120" long and anodized duraluminum, 3-15/16" in diameter, weighing 22 lbs. Net shall attach at only two points on the sliding O-Rail, which shall be mounted in profiled grooves running infinitely over the full range. A two position (lock/off) lever lock shall be used to provide slip-free adjustment of the net height; screw-in adjustment knobs shall be deemed unacceptable. Uprights shall adjust to allow for mens', womens', and juniors' heights, as well as for badminton and tennis set ups. Uprights shall have floor-protective molded plastic caps.

COLLEGIATE 4000 POST WITH WINCH

MODEL NO. SNAVB41C4W

Removable type, in-floor sleeves. Uprights shall be one single piece, 120" long and shall be anodized duraluminum, 3-15/16" in diameter, weighing 28 lbs. Net shall attach at only two points on the sliding N-Rail, which shall be mounted in profiled grooves running infinitely over the full range. Net tensioning device shall be mounted on the N-Rail, and shall be a low profile, non-slip threaded-rod type, utilizing conical toothed steel gears for safety and durability. The range of this gear mechanism shall be 17-½". Gear mechanism shall be completely encased in anodized duraluminum. A two position (lock/off) lever lock shall be used to provide slip-free adjustment of the net height; screw-in adjustment knobs shall be deemed unacceptable. Uprights shall have floor-protective molded plastic caps. Uprights shall adjust to allow for mens', womens', and juniors' heights, as well as for badminton and tennis set ups. Hand cranks shall be permanently attached.

COLLEGIATE 4000 CENTER POST

MODEL NO. SNAVB45C4N

Removable type, in floor sleeves. Uprights shall be one single piece, 120" long and shall be anodized duraluminum, 3-15/16" in diameter, weighing 28 lbs. Center uprights shall have O-Rail net attachments on two sides of this upright. Rails shall move independently of each other, allowing different net heights on each side of the uprights. Uprights shall adjust to allow for mens', womens', and juniors' heights, as well as for badminton and tennis set ups. Uprights shall have floor-protective molded plastic caps.

COLLEGIATE 4000 CENTER POST WITH WINCH

MODEL NO. SNAVB45C4W

Removable type, in floor sleeves. Uprights shall be one single piece, 120" long and shall be anodized duraluminum, 3-15/16" in diameter, weighing 28 lbs. Center uprights shall have rail net attachments on two sides of the upright. Rails shall move independently of each other, allowing different net heights on each side of the uprights. Net shall attach at only two points on the sliding N-Rail, which shall be mounted in profiled grooves running the full length of the upright, thus allowing the rail to be adjusted infinitely over the full range. The net tensioning device shall be mounted on the N-Rail, and shall be a low profile non-slip threaded-rod type, utilizing conical-toothed gears of hard steel for safety and durability. The range of this gear mechanism shall be 17-½". Gear mechanism and threaded rod shall be completely encased in anodized aluminum. A two position (lock/off) lever lock shall be used to provide slip-free adjustment of the net height; screw-in adjustment knobs shall be deemed unacceptable. Uprights shall have floor-protective molded plastic caps. Uprights shall adjust to allow for mens', womens', and juniors' heights, as well as for badminton and tennis set ups. Hand cranks shall be permanently attached.

VOLLEYBALL FLOOR SLEEVE

MODEL NO. VB25SL

Steel sleeve shall be 13" long. Inside diameter of the sleeve shall be 4".

UNIVERSAL HINGED BRASS COVER PLATE

MODEL NO. VB23CV

Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

INTERNATIONAL NET WITH RATCHET TENSIONER

MODEL NO. SNAVB1298A

Net shall be 9.8 meters in length and 1-meter maximum width. Netting shall be 10 centimeters square mesh, black nylon, KNOTLESS. Wide side tapes with sewn-in wooden dowels for equal net tension. Top cable shall be 1/8" steel, specially sewn into 50-millimeter white nylon binding. Bottom tension rope shall be nylon, covered by 30-millimeter white nylon binding.

NET ANTENNAE WITH SIDELINE MARKERS

MODEL NO. SNAVB12

Net antennae shall be 3/8" in diameter fiberglass rods, 71" long, with alternating red and white bands. Sideline markers shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to contain antennae. Attachment to the net shall be full-length Velcro closures.

CABLE COVERS

MODEL NO. SNAVB35P

Cable covers shall be made of 1/2" thick polyurethane foam. Shall be covered in 14 oz. reinforced polyester laminated white vinyl.

POST SAFETY PADS

MODEL NO. SNAVB51P

Each post pad shall be a single piece, 72" in height and 26" in width. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to posts shall be effected by Velcro straps. 16 colors available: scarlet, orange, burnt orange, kelly green, forest green, royal blue, navy blue, Columbia blue, purple, maroon, black, gray, cardinal, brown, gold and vegas gold.

CENTER POST SAFETY PADS

MODEL NO. SNAVB510P

Same specifications exist as the model 67815 post pad. Exception: each center post pad shall consist of two identical pieces, 72" in height and 10.5" in width. Attachment to the posts shall be effected by Velcro straps that are attached on both pads. 16 colors available: scarlet, orange, burnt orange, kelly green, forest green, royal blue, navy blue, Columbia blue, purple, maroon, black, gray, cardinal, brown, gold and vegas gold.

VB73 REFEREE STAND WITH PADS

MODEL NO. VB73

Shall be of tubular steel construction with steel platform. Stand shall attach to the upright by means of a heavy-duty steel clamp with rubber pads to protect the upright. Clamp shall close by means of a threaded rod-driven mechanism, and shall fold away when not in use. Stand shall have wheels to allow for easy transport. **Available in Grey, Black, Red, Maroon, Royal Blue, and Navy Blue.**