

## **Architectural Specifications Floor Sleeve Systems**

### **UNIVERSAL VOLLEYBALL FLOOR SLEEVE**

#### **MODEL NO. VB25SL**

Steel sleeve shall be 13" long. Inside diameter of the sleeve shall be 4".

### **UNIVERSAL HINGED BRASS COVER PLATE**

#### **MODEL NO. VB23CV**

Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

### **UNIVERSAL VOLLEYBALL FLOOR SLEEVE AND HINGED BRASS COVER PLATE**

#### **MODEL NO. VB27**

This package shall include both the VB25SL floor sleeve and VB23CV cover plate listed above

### **VOLLEYBALL T-BASE**

#### **MODEL NO. SNATBASE - RECOMMENDED APPLICATION:**

Designed for use in facilities where the sub-floor structure is not adequate to accommodate the installation of a floor sleeve. T-Base shall be constructed of welded steel capable of accepting a 4" diameter volleyball post. The gross dimensions will be 12" H x 17 3/4"L x 18"W. The base is securely locked in place with a 1/2" turn bolt screwed into a 1/2" diameter, 13 thread-per-inch floor anchor.

### **T-BASE PADDING**

#### **MODEL NO. VBTBASEP**

Each T-Base pad shall be two pieces – one wrap-around pad for T-Base sides, and one trapezoidal pad for T-Base top. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to each other shall be effected by Velcro. 10 colors available: red, orange, yellow, kelly green, forest green, royal blue, navy blue, purple, maroon, and black.